

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/001260 A1

(51) International Patent Classification⁷: **F16K 3/26**,
I/12, 47/08

Joseph [GB/GB]; 17 Balmoral Road, New Longton,
Preston, Lancashire PR4 4JJ (GB).

(21) International Application Number:
PCT/GB2003/002239

(74) Agents: **MANSFIELD, Peter, Turquand et al.**; Patents
Dept, 329 Harwell, Didcot, Oxfordshire OX11 0QJ (GB).

(22) International Filing Date: 22 May 2003 (22.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0214597.7 25 June 2002 (25.06.2002) GB

(71) Applicant (for all designated States except US): **ACCEN-
TUS PLC** [GB/GB]; 329 Harwell, Didcot, Oxfordshire
OX11 0QJ (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BOWE, Michael**,

(54) Title: VALVE ASSEMBLY



(57) **Abstract:** A valve assembly (10) comprises a valve stem (14) with a bore (15) and radial apertures (17), and a sleeve (18) closed at one end and slidable over the valve stem (14) to obstruct the apertures (17). At the end of the valve stem opposite the outlet end, the valve stem (14) defines a fluidic vortex chamber (22) with both tangential inlets (28) and non-tangential peripheral inlets (26), and with an axial outlet (24) communicating with the bore (15). The sleeve (18) defines at least one radial port (32) near its closed end. The valve assembly operates in a conventional fashion except when approaching closure. Once the last of the apertures (17) in the valve stem has been closed, the only flow path is through the fluidic vortex chamber (22). Further movement of the sleeve (18) alters the distribution of the flow between the non-tangential inlets (26) and the tangential inlets (28), so adjusting the strength of the fluidic vortex and the resistance to fluid flow. The valve assembly (10) suppresses erosive and cavitation wear of the valve mechanism, and can provide a wide range of flow modulation.